



**PRODUCT DATA SHEET**

- NO ODOR
- AGGRESSIVE ADHESIVE
- FAST & EASY APPLICATION
- IDEAL FOR TPO, PVC & HYPALON ROOFS
- GREAT FOR SEALING, PATCHING & EMERGENCY REPAIRS

**RXT WHITE**  
**PREMIUM SELF-ADHESIVE REPAIR**  
**& FLASHING TAPE**

MADE WITH  
**SHUR-STIK**  
**PERMANENT ADHESIVE**

**DESCRIPTION:**

Roof X Tender™ White Premium Repair Tape with Shur-Stik Adhesive Technology is an aggressive self-adhesive repair and flashing tape designed to immediately stop leaks and make a variety of roofing and waterproofing repairs. It will adhere to metal, wood, structural concrete, concrete block, brick, smooth BUR, smooth SBS, smooth APP, EPDM, TPO, Hypalon and PVC roofs. Manufactured with select thermoplastic elastomers, Roof X Tender Shur-Stik Tape provides a tough and durable repair. It's pressure sensitive properties allow a fast, clean and easy application.

**PREPARATION:**

Substrate should be clean, dry and free of dew, frost, oil, salt, dust and rust. Clean area first with a cloth and cleaner. On single ply roofs clean with rags and acetone to remove any oil or grime. Use a wire brush to remove loose granules on SBS & APP mod-bit sheets. Seal edges with white sealant to stop water migration between the granules and the tape. In cold temperature conditions (-30°F to 40°F), use RX-99 primer on single ply and metal surfaces.

**APPLICATION:**

In cold climates, preheat roll in a warm room and warm the substrate with hot air. In extreme cold weather keep the rolls warm to aid adhesion. In hot weather (80°F+) keep rolls in a cooler and/or shade to aid in application. Cut to length. Shorter lengths (less than 4 ft) are easier to work with unless using a team of two or more applicators. Remove release film. Press in place using a gloved hand or a steel roller. Apply the exact length to predetermined location. Tape cannot be peeled up and reset. Always roll from the center out to remove trapped air pockets and fishmouths. Start in corners to eliminate "tenting". When applying in temperatures between -30°F and 40°F, apply RX-99 primer prior to installation of tape.

**PRECAUTIONS:**

RXT White Premium Repair Tape will not adhere to silicone surfaces. For best results, test adhesion on membranes before applying. Do NOT store at temperatures above 110°F. Do NOT stretch tape during installation. Do NOT use where acidic or alkaline chemicals are present (for example: lab fume hoods, vents, etc).

**TECHNICAL DATA:**

<b>Peel Strength</b> 21 lbs. +/- in width	<b>Shelf Life</b> 5 years*
<b>Application Temperature</b> - 30 ° F to 200 ° F	<b>Tensile Break</b> 4000+/- 500 psi
<b>Color</b> White	<b>Total Thickness</b> 35 mils
<b>Elongation</b> 900%	<b>UV Resistance</b> Excellent
<b>Low Temperature Flexibility</b> Passes at - 65 ° F, no cracking	<small>*Storage at ambient room temperatures</small>
<b>Permeability</b> .001 perms max	

**SHIPPING:**

<b>4" X 50' ROLLS</b> 12 per case	<b>6" X 50' ROLLS</b> 8 per case	<b>12" X 50' ROLLS</b> 4 per case
--------------------------------------	-------------------------------------	--------------------------------------

**WARRANTY & DISCLAIMER:**

For limited warranty and disclaimer information visit:  
[www.roofxtender.com/warranty.html](http://www.roofxtender.com/warranty.html)

